



<b>1/2" 1.4/4.5mm C</b>		<b>1/3"</b>	
Focal Length		f=4.5mm±5%	
Max. Diameter (Ratio)		F=1 : 1.4±5%	
Element		6 Group 7 Elements	
Picture Size		4.8x6.4mm	3.6x4.8
Angle	Ver.	59.4°	45.1°
	Hol.	79.0°	59.7°
	Dia.	98.2°	74.5°
Distortion (TV)		-17.5%	
Shooting Range at M.O.D	Ver.	180mm	
	Hol.	260mm	
	Dia,	364mm	
Minimum Object Distance		0.2m	
Flange Back		17.526 mm in air	
Back Focus		9.96mm in air	
Filter Screw Size			
Front/Rear Effective Dia.		Front: φ 15.1mm	Rear: φ 10.1mm
Mount		C-MOUNT	
Exit Pupil		-17.5mm	
Temperature Range		-10~+45° C	
Strong Temperature Range		-40~+60° C	
Resolution		Center:100Line/mm	Corner: 60Line/mm
Stopper Strength		10kgf · cm	
Endurance Tests		Iris:5,000Times	Focus:5,000Times
Operating Torque		Iris:50~600gf · cm	Focus:100~1000gf · cm
Weight		71g±5g	



1/2" 1.4/4.5mm
LM5NCL