



| 2/3" 1.4/12mm C | | 1/2" | 1/3" |
|---------------------------|------------|------------------------|------------------|
| FOCAL LENGTH | | f=12mm | |
| MAX. DIAMETER (RATIO) | | F=1:1.4~16 | |
| ELEMENT | | 6 Elements in 6 Groups | |
| PICTURE SIZE | | 6.6x8.8mm | 4.8x6.4 3.6x4.8 |
| ANGLE | VER. ANGLE | 31.7° | 23.0° 17.2° |
| | HOR. ANGLE | 42.5° | 30.7° 23.0° |
| | DIA. ANGLE | 53.7° | 38.5° 28.8° |
| DISTORTION (TV) | | -2.5% | -1.2% -0.6% |
| SHOOTING RANGE AT | VER. | 117mm | 84mm 62mm |
| MINIMUM FOCUS | HOR. | 161mm | 113mm 84mm |
| DISTANCE | DIA. | 209mm | 145mm 106mm |
| MINIMUM FOCUS DISTANCE | | 0.1m | 0.2m 光学保証範囲 |
| FLANGE BACK | | 17.526 | mm in air |
| BACK FOCUS | | 11.12mm | in air |
| FILTER SCREW SIZE | | M27x0.5 | |
| FRONT/REAR EFFECTIVE DIA. | | Front: Ø 12.3mm | Rear: Ø 11.7mm |
| MOUNT | | C-MOUNT | |
| EXIT PUPIL | | -38.9mm | |
| TEMPERATURE RANGE | | -10~+45°C | |
| STORNG TEMPERATURE RANGE | | -40~+60°C | |
| RESOLUTION CENTER/CORNER | | Center 100line/mm | Corner 60line/mm |
| WEIGHT | | 63g | |

注) 本仕様書については、予告なしに変更する場合があります。



| | | | | | |
|----------|-------|-----|---------------|----|----|
| | | 尺度 | 1/1 | 承認 | 製図 |
| | | 機種名 | LM12JC | | |
| | | 機種番 | 2/3" 1.4/12mm | | |
| 04.12.21 | 作成年月日 | | | | |