



2/3" 1.4/16mm C		1/2"	1/3"
FOCAL LENGTH		f=16mm	
MAX. DIAMETER (RATIO)		F=1:1.4~16	
ELEMENT		6 Elements in 6 Groups	
PICTURE SIZE		6.6x8.8mm	3.6x4.8
ANGLE	VER. ANGLE	22.8°	12.4°
	HOR. ANGLE	30.5°	16.6°
	DIA. ANGLE	38.3°	20.8°
DISTORTION		-1.5%	-0.4%
SHOOTING RANGE AT	VER.	82.6mm	44.5mm
MINIMUM FOCUS	HOR.	111.8mm	59.6mm
DISTANCE	DIA.	142.5mm	74.9mm
MINIMUM FOCUS DISTANCE		0.1m	0.2m 光学保証範囲
FLANGE BACK		17.526 mm	in air
BACK FOCUS		12.15mm	in air
FILTER SCREW SIZE		M27x0.5	
FRONT/REAR EFFECTIVE DIA.		Front: Ø 12.0mm	Rear: Ø 12.8mm
MOUNT		C-MOUNT	
EXIT PUPIL		-48.9mm	
TEMPERATURE RANGE		-10~+45°C	
STORAGE TEMPERATURE RANGE		-40~+60°C	
RESOLUTION CENTER/CORNER		Center 100line/mm	Corner 60line/mm
WEIGHT		55g	

注) 本仕様書については、予告なしに変更する場合があります。



		尺度 1/1	承認	製図
		機種名	LM16JC	
05.6.23	作成年月日	機種番	2/3" 1.4/16mm	