



| φ23 2.0/50mm C | | |
|---------------------------|------------|--------------------------------|
| FOCAL LENGTH | | f=50mm |
| MAX. DIAMETER (RATIO) | | F=1:2.0~22 |
| ELEMENT | | 6 GROUPS 7 ELEMENTS |
| PICTURE SIZE | | 13.8x18.4mm |
| ANGLE | VER. ANGLE | 15.7° |
| | HOR. ANGLE | 20.6° |
| | DIA. ANGLE | 25.4° |
| DISTORTION (TV) | | 0.8% |
| SHOOTING RANGE AT | VER. | 75mm |
| MINIMUM FOCUS | HOR. | 100mm |
| DISTANCE | DIA. | 124mm |
| MINIMUM FOCUS DISTANCE | | 0.3m |
| FLANGE BACK | | 17.526mm in air |
| BACK FOCUS | | 21.6mm in air |
| FILTER SCREW SIZE | | M37.5x0.5 |
| FRONT/REAR EFFECTIVE DIA. | | FRONT φ31.8mm REAR φ16.0mm |
| MOUNT | | C-MOUNT |
| EXIT PUPIL | | -19.1mm |
| TEMPERATURE RANGE | | -10~+50° C |
| STORAGE TEMPERATURE RANGE | | -20~+60° C |
| RESOLUTION CENTER/CORNER | | Center 160lp/mm Corner 80lp/mm |
| LENS COATING | | WIDE BAND MULTI COATING |
| WEIGHT | | 220 g |

NOTE: Specifications and availability are subject to change without notice

注) 本仕様については、予告なしに変更する場合があります。



| | | | | | | | |
|------------|-------|-----|----------------------|----|----|---|----|
| | | 尺度 | 1/1 | 承認 | 八木 | 製 | 富永 |
| | | 機種名 | 4/3(φ23) F2.0 f=50mm | | | | |
| | | 機種番 | LM50XC | | | | |
| 2010.11.04 | 作成年月日 | | | | | | |