



φ23 2.0/12mm C		
FOCAL LENGTH		f=12mm
MAX. DIAMETER (RATIO)		F=1:2.0~22
ELEMENT		10 GROUPS 12 ELEMENTS
PICTURE SIZE		13.8x18.4mm
ANGLE	VER. ANGLE	59.6°
	HOR. ANGLE	74.9°
	DIA. ANGLE	86.8°
DISTORTION (TV)		0.59%
SHOOTING RANGE AT	VER.	136 mm
MINIMUM FOCUS	HOR.	182 mm
DISTANCE	DIA.	225 mm
MINIMUM FOCUS DISTANCE		0.1m
FLANGE BACK		17.526mm in air
BACK FOCUS		13.0mm in air
FILTER SCREW SIZE		M55x0.75
FRONT/REAR EFFECTIVE DIA.		FRONT φ44.8mm REAR φ16.0mm
MOUNT		C-MOUNT
EXIT PUPIL		-31.8mm
TEMPERATURE RANGE		-10~+50° C
STORAGE TEMPERATURE RANGE		-20~+60° C
RESOLUTION CENTER/CORNER		Center 160lp/mm Corner 80lp/mm
LENS COATING		WIDE BAND MULTI COATING
WEIGHT		270 g

NOTE: Specifications and availability are subject to change without notice

注) 本仕様については、予告なしに変更する場合があります。



	尺度	1/1	承認	八木	製	富永
	機種名	4/3(φ23) F2.0 f=12mm				
	機種番	LM12XC				
2010.11.04	作成年月日					