



φ23 2.0/25mm C		
FOCAL LENGTH		f=25mm
MAX. DIAMETER (RATIO)		F=1:2.0~16
ELEMENT		6 GROUPS 8 ELEMENTS
PICTURE SIZE		13.8x18.4mm
ANGLE	VER. ANGLE	31.1°
	HOR. ANGLE	40.9°
	DIA. ANGLE	50.2°
DISTORTION (TV)		-0.57%
SHOOTING RANGE AT	VER.	93mm
	HOR.	125mm
MINIMUM FOCUS DISTANCE	DIA.	157mm
		0.15m
FLANGE BACK		17.526mm in air
BACK FOCUS		24.3mm in air
FILTER SCREW SIZE		M40.5x0.5
FRONT/REAR EFFECTIVE DIA.		FRONT φ31.4mm REAR φ18.2mm
MOUNT		C-MOUNT
EXIT PUPIL		-63.9mm
TEMPERATURE RANGE		-10~+50° C
STORAGE TEMPERATURE RANGE		-20~+60° C
RESOLUTION CENTER/CORNER		Center 160lp/mm Corner 80lp/mm
LENS COATING		WIDE BAND MULTI COATING
WEIGHT		250 g

NOTE: Specifications and availability are subject to change without notice

注) 本仕様については、予告なしに変更する場合があります。



		尺度	1/1	承認	八木	製	富永
		機種名	4/3(φ23) F2.0 f=25mm				
		機種番	LM25XC				
2010.11.03		作成年月日					