

| 型番 | Product Name | CF35ZA-1S |
|--------------------------|--|----------------------|
| 焦点距離 [mm] | Focal length [mm] (design value) | 35 (34.78) |
| 絞り範囲 (F値) | Iris range (Fnumber) | F1.8-F16 |
| 画角 (H × V) | Angle of view | 23.0° × 17.3° (1.1") |
| フォーカス範囲 (レンズメカ先端より) [mm] | Working distance (from front of lens barrel) [mm] | ∞ - 200 |
| 操作方法:フォーカス | Operation of focus | Manual |
| 操作方法:アイリス | Operation of iris | Manual |
| フィルタ径 [mm] | Filter thread [mm] | M37.5 × 0.5 |
| マウント | Mount | C-mount |
| 質量 (約) [g] | Weight (approx.) [g] | 165 |
| 適合センサーサイズ (標準) | Sensor size (std.) | 1.1" (2.5μm) |
| 適合センサーサイズ (最大) | Sensor size (max.) | 4/3" (3.45μm) |
| バックフォーカス (空気換算長) [mm] | Back focal length (in air) [mm] | 21.30 |
| フランジバック [mm] | Flange back [mm] | 17.526 |
| 入射瞳位置 (マウント面から) [mm] | Entrance pupil position (from Mount) [mm] | -26.59 |
| 射出瞳位置 (結像面より) [mm] | Exit pupil position (from image plane) [mm] | -102.02 |
| 前側主点 (マウント面から) [mm] | Front principal point (from Mount) [mm] | -4.54 |
| 後側主点 (マウント面から) [mm] | Rear principal point (from Mount) [mm] | -17.25 |
| 主点間隔 [mm] | Distance between the principal points [mm] | -12.71 |
| TV歪み [%] | TV distortion [%] | -0.32 |
| 外形寸法 [mm] | Dimension [mm] | φ39 × 67.3 |
| 主光線入射角度 [°] | Chief Ray Angle [°] | 4.53 |
| 周辺光量比 (F4.0・対角端) [%] | Relative illumination [%] (Aperture: F4.0, Image height : at diagonal) | 93 |
| 周辺光量比 (開放・対角端) [%] | Relative illumination [%] (Aperture: at full open, Image height : at diagonal) | 37 |
| 使用温度範囲 | Operation Temperature Range | -10℃ ~ +50℃ |
| 保存温度範囲 | Storage Temperature Range | -30℃ ~ +60℃ |

These specifications are subject to change without notice.

28-Feb-20