



| | | | | |
|---|-----------|---------------------------------|-------------|-------------|
| 2/3" 2.8/12mm C | | 2/3" | 1/1.8" | 1/2" |
| FOCAL LENGTH | | f=12mm | | |
| F-NUMBER | | F=2.8-16 | | |
| PICTURE SIZE | | 6.6 × 8.8mm | 5.4 × 7.2mm | 4.8 × 6.4mm |
| ANGLE OF VIEW (∞) | VER.ANGLE | 31.2° | 25.6° | 22.8° |
| | HOR.ANGLE | 41.0° | 33.9° | 30.3° |
| | DIA.ANGLE | 50.2° | 41.9° | 37.5° |
| DISTORSION (TV) | | -0.43% | -0.46% | -0.42% |
| FIELD OF VIEW (MINIMUM FOCUS DISTANCE) | VER. | 118mm | 96mm | 86mm |
| | HOR. | 159mm | 129mm | 115mm |
| | DIA. | 200mm | 163mm | 144mm |
| MINIMUM FOCUS DISTANCE | | 0.2m | | |
| FLANGE BACK | | 17.526mm in air | | |
| BACK FOCUS | | 12.6mm in air | | |
| FILTER SCREW SIZE | | None | | |
| FRONT/REAR EFFECTIVE DIA. | | FRONT φ18.5mm REAR φ13.5mm | | |
| MOUNT | | C-MOUNT | | |
| EXIT PUPIL | | -58.7mm | | |
| TEMPERATURE RANGE | | -10~+50°C | | |
| STORAGE TEMPERATURE RANGE | | -20~+60°C | | |
| RESOLUTION CENTER/CORNER | | CENTER 160lp/mm CORNER 100lp/mm | | |
| WEIGHT | | 55g | | |

NOTE: Specifications and availability are subject to change without notice

注) 本仕様については、予告なしに変更する場合があります。



| | | | | | |
|------------|------|-------------|----------------------|------------------|---------|
| | | 尺 度 | 1:1 | 工 場 番 号 | S10-633 |
| | | 機 種 名 | 2/3" f=12mm F2.8 5MP | | |
| 2019/09/26 | 誤記訂正 | 機 種 番 | LM12JC5MC 外觀図 | | |
| 2019/02/08 | 作成 | | | | |
| 日付 | 内容 | | | | |