

This vibration-resistant lens is designed for use with large-area and line-scan sensors in harsh conditions, as encountered in many industrial applications. Its highly homogeneous imaging performance across the entire image field, combined with low chromatic aberrations and geometric distortions, ensures very high image quality across a wide magnification range. The V38 mount is compatible with the modular V38 system and its wide range of accessories, including focusing mounts, extension tubes and camera adapters.

## Key features

- Uniform MTF from center to edge
- Low distortion
- Low chromatic aberrations
- Large image circle

## Applications


- Machine Vision
- AOI (Automated Optical Inspection)
- FPD/PCB inspection
- Logistics

## Technical specifications


Type [standard]	V38
ID [standard]	1111934
Interface	V38-Mount
Focal length [mm]	40
F/# range	F/2.8 ... F/22
Numerical aperture [object   image]	-   0.16
Max. sensor size [mm]	43.2
Max. angle of view [°]	57
Rec. magnification range	-0.25 ... 0
Rec. working distance range [mm]	175 ... ∞
Max. mechanical focus travel [mm]	-
Filter thread [mm]	M37 x 0.75
Storage temperature [°C]	-25 ... +70
Net. weight [g]	105
Additional info	-
f'eff [mm]	39.96
SF [mm]	-27.10
S'F' [mm]	29.91
HH' [mm]	-1.09
β'P	1.04
SEP [mm]	11.49
S'AP [mm]	-11.48
Σd [mm]	21.83

## MTF charts


Spectrum name	VIS					
Wavelengths [nm]	425	475	525	575	625	675
Rel. weights [%]	8	16	23	22	19	13




## Rel. illumination vs. image height




## Distortion vs. image height



## Transmittance vs. wavelength



## Technical drawings



Accessories	Mount	Eff. length	ID
UNIFOC 12	V38 / V38	17.4 – 29.4 mm	11726
UNIFOC 7	V38 / V38	20 – 27 mm	1001041
UNIFOC 7	V38 / M58 x 0.75	20 – 27 mm	1054532
UNIFOC 5	V38 / C-Mount	19.2 – 24.2 mm	1011634
Adapter	V38 / C-Mount	6.5 mm	20052
	V38 / TFL	6.5 mm	1098491
	V38 / M37 x 0.75	3.5 mm	1100587
	V38 / L	6.5 mm	20054
	V38 / M42 x 0.75	6.5 mm	20053
	V38 / M42 x 1	6.5 mm	20059
	V38 / M42 x 1	35 mm	1001692
	V38 / M58 x 0.75	10 mm	1018385
	V38 / F	9.3 mm	21610
	Extension tube	V38 / V38	6 mm
V38 / V38		8 mm	20177
V38 / V38		10 mm	20178
V38 / V38		25 mm	20179
V38 / V38		50 mm	20154
V38 / V38		75 mm	20155

Annotation	
Focal length	Nominal focal length
F/# range	Image space F-number range for infinity focus position
Numerical aperture	Maximum real numerical aperture (depending on recommended magnification range either for infinity or respective fixed magnification)
Max. sensor size	Image circle diameter
Max. angle of view	Angle of view associated with maximum sensor size (depending on recommended magnification range either for infinity or respective fixed magnification)
Rec. magnification range	Magnification range as recommended by Schneider-Kreuznach
Rec. working distance range	Working distance, i.e. distance between object and first mechanical element, associated with recommended magnification range
Max. mechanical focus travel	Maximum possible movement of the lens from infinity position (depending on recommended magnification range either for infinity or respective fixed magnification)
Net weight	weight of unpacked lens without lens cap
$f'_{\text{eff}}$	Effective focal length
SF	Distance between vertex of first lens surface and object space focal point
S'F'	Distance between vertex of last lens surface and image space focal point (back focal distance at infinity)
HH'	Distance between principal planes
$\beta'P$	Pupil magnification (= exit pupil diameter / entrance pupil diameter)
SEP	Distance between vertex of first lens surface and entrance pupil
S'AP	Distance between vertex of last lens surface and exit pupil
$\Sigma d$	Distance between vertices of first and last lens surface
s'A	Flange focal distance (in air) for infinite object distance (depending on recommended magnification range either for infinity or respective fixed magnification)
$\beta'$	Magnification (= image size / object size), negative value because image is inverted
OO'	Distance between object and image

Unless otherwise stated all dimensions in this data sheet are in mm.

## Headquarters Europe

### **Jos. Schneider Optische Werke GmbH**

Ringstraße 132

55543 Bad Kreuznach

☎ +49 671 601 205

✉ [cs@schneiderkreuznach.com](mailto:cs@schneiderkreuznach.com)

[www.schneiderkreuznach.com](http://www.schneiderkreuznach.com)

## Offices Worldwide

### **America**

☎ +1 800 645 7239 (East Coast)

☎ +1 800 228 1254 (West Coast)

✉ [info@schneideroptics.com](mailto:info@schneideroptics.com)

### **Asia**

☎ +86 755 8832 1170

✉ [info@schneider-asiapacific.com](mailto:info@schneider-asiapacific.com)